

Task: KIN

Movie-goer

Farias Brito High School Programming Camp, Day 5. Available memory: 128 MB. 29.07.2016

Byteasar is an avid movie-goer, so he was pleased to find out that his favorite studio cinema will be running a summer movie marathon. Each of the n days of the summer, one out of m movies will be screened. A marathon pass entitles one to see any number of movies, provided that the pass holder does not skip a day, i.e., skipping one invalidates the pass. One can, however, choose their first day freely.

Based on Internet reviews, Byteasar has assigned each of the m movies a score. Now he would like to use his summer pass so as to maximize the total score of the movies he sees. What makes this a challenging task is the fact that Byteasar cannot stand watching the same movie again. Watching a movie again not only bores him, but also deprives him of all the fond memories previously associated with the movie. Thus, in fact he wants to maximize the total score of the movies he will see exactly once.

Input

In the first line of the input, there are two integers, n and m ($1 \leq m \leq n$), separated by a single space, that specify the length of the summer movie marathon and the number of movies, respectively. For ease of notation, we number the movies from 1 to m .

In the second line, there is a sequence of n integers, f_1, f_2, \dots, f_n ($1 \leq f_i \leq m$), separated by single spaces: f_i is the number of the movie screened on the i -th day of the marathon. In the third line, there is a sequence of m integers, w_1, w_2, \dots, w_m ($1 \leq w_j \leq 1\,000\,000$), separated by single spaces: w_j is the score of the movie number j . Note that it may happen that some of the m movies will not be screened at all during the marathon.

Output

In the first and only line of the output, a single number should be printed, equal to the maximal total score of the movies Byteasar can watch exactly once with his summer movie marathon pass.

Example

For the input data:

```
9 4
2 3 1 1 4 1 2 4 1
5 3 6 6
```

the correct result is:

```
15
```

Explanation of the example: Byteasar can use his pass to watch 6 movies, starting on the second day of the marathon. This way, he will see the movies number 2, 3, and 4 exactly once.

Grading

Subtask	Constraints	Points
1	$n \leq 8000$	20
2	$n \leq 100\,000$	40
3	$n \leq 1\,000\,000$	40